
STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING						FORM 3 AMENDED REPORT			
APPLI	CATION FOR	PERMIT TO DRILL				1. WELL NAME and NUMBER NBU 920-21P			
2. TYPE OF WORK DRILL NEW WELL	REENTER P8	AA WELL DEEPE	N WELL			3. FIELD OR WILD	CAT NATURAL BUTTES		
4. TYPE OF WELL Gas We	ell Coalb	ed Methane Well: NO					NITIZATION AGREI NATURAL BUTTES	EMENT NAME	
6. NAME OF OPERATOR KERF	R-MCGEE OIL & O	GAS ONSHORE, L.P.				7. OPERATOR PHO	NE 720 929-6587		
8. ADDRESS OF OPERATOR		Denver, CO, 80217				9. OPERATOR E-MA		com	
10. MINERAL LEASE NUMBER	. BOX 173773, B	11. MINERAL OWNE	RSHIP	_	_	12. SURFACE OWN			
(FEDERAL, INDIAN, OR STATE) UTU 0144869		FEDERAL (IND:	IAN STATE	<u> </u>	FEE (FEDERAL IN	DIAN 📵 STATE (FEE (
13. NAME OF SURFACE OWNER (if box 12	= 'fee')					14. SURFACE OWN	ER PHONE (if box 1	2 = 'fee')	
15. ADDRESS OF SURFACE OWNER (if box	12 = 'fee')					16. SURFACE OWN	ER E-MAIL (if box 1	.2 = 'fee')	
17. INDIAN ALLOTTEE OR TRIBE NAME		18. INTEND TO COM		TION	FROM	19. SLANT			
(if box 12 = 'INDIAN') Ute Tribe			ommingling Applica	tion)	NO 🗍	VERTICAL 📵 DI	RECTIONAL (HO	ORIZONTAL 🗐	
20. LOCATION OF WELL	FO	OOTAGES	QTR-QTR		SECTION	TOWNSHIP	RANGE	MERIDIAN	
LOCATION AT SURFACE	281 F	SL 524 FEL	SESE		21	9.0 S	20.0 E	S	
Top of Uppermost Producing Zone	281 F	SL 524 FEL	SESE		21	9.0 S	20.0 E	S	
At Total Depth	281 F	SL 524 FEL	SESE		21	9.0 S	20.0 E	S	
21. COUNTY UINTAH		22. DISTANCE TO NE	EAREST LEASE LII	NE (F	eet)	23. NUMBER OF AC	RES IN DRILLING U	JNIT	
		25. DISTANCE TO NE (Applied For Drilling		SAME	POOL	26. PROPOSED DEPTH MD: 10483 TVD: 10483			
27. ELEVATION - GROUND LEVEL		28. BOND NUMBER				29. SOURCE OF DRILLING WATER / WATER RIGHTS APPROVAL NUMBER IF APPLICABLE Permit #43-8496			
4814			WYB000291				remii: #43-0490		
		АТ	TACHMENTS						
VERIFY THE FOLLOWING	ARE ATTACH	ED IN ACCORDANG	CE WITH THE U	ТАН	OIL AND G	GAS CONSERVAT	ON GENERAL RU	ILES	
✓ WELL PLAT OR MAP PREPARED BY	LICENSED SUR	EVEYOR OR ENGINEER	cor	COMPLETE DRILLING PLAN					
AFFIDAVIT OF STATUS OF SURFACE	OWNER AGRE	EMENT (IF FEE SURF	ACE) FOR	FORM 5. IF OPERATOR IS OTHER THAN THE LEASE OWNER					
DIRECTIONAL SURVEY PLAN (IF DIRECTIONALLY OR HORIZONTALLY DRILLED)				TOPOGRAPHICAL MAP					
NAME Danielle Piernot TITLE Regulatory Analyst					PHONE 720	929-6156			
SIGNATURE DATE 08/06/2009					EMAIL danie	elle.piernot@anadark	o.com		
API NUMBER ASSIGNED 43047506270000	Al	PPROVAL			bell	ogill			
Pe					Perm	Permit Manager			

API Well No: 43047506270000 Received: 8/6/2009

	Proposed Hole, Casing, and Cement								
String	Hole Size	Casing Size	Top (MD)	Bottom (MD)					
Prod	7.875	4.5	0	10483					
Pipe	Grade	Length	Weight						
	Grade HCP-110 LT&C	883	11.6						
	Grade I-80 LT&C	9600	11.6						

API Well No: 43047506270000 Received: 8/6/2009

	Proposed Hole, Casing, and Cement								
String	Hole Size	Casing Size	Top (MD)	Bottom (MD)					
Surf	12.25	9.625	0	2615					
Pipe	Grade	Length	Weight						
	Grade J-55 LT&C	2615	36.0						



NBU 920-21P

Surface: 281' FSL 524' FEL (SE/4SE/4)

Sec. 21 T9S R20E

Uintah, Utah Mineral Lease: UTU 0144869

ONSHORE ORDER NO. 1

DRILLING PROGRAM

1. – 2. Estimated Tops of Important Geologic Markers: Estimated Depths of Anticipated Water, Oil, Gas, or Mineral Formations:

<u>Formation</u>	<u>Depth</u>	Resource
Uinta Green River Birds Nest Mahogany Wasatch Mesaverde	0 – Surface 1,676' 1,903' 2,414' 5,093' 8,418'	Water Water Gas Gas
MVU2 MVL1	9,384' 9,860'	Gas Gas
TD	10,483'	

3. Pressure Control Equipment (Schematic Attached)

Please refer to the attached Drilling Program.

4. **Proposed Casing & Cementing Program:**

Please refer to the attached Drilling Program.

5. <u>Drilling Fluids Program:</u>

Please refer to the attached Drilling Program.

Evaluation Program:

Please refer to the attached Drilling Program.

7. <u>Abnormal Conditions</u>:

Maximum anticipated bottomhole pressure calculated at 10,483' TD, approximately equals 6,531 psi (calculated at 0.62 psi/foot).

Maximum anticipated surface pressure equals approximately 4,225 psi (bottomhole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

8. <u>Anticipated Starting Dates:</u>

Drilling is planned to commence immediately upon approval of this application.

9. <u>Variances:</u>

Please refer to the attached Drilling Program.

Onshore Order #2 – Air Drilling Variance

Kerr-McGee Oil & Gas Onshore LP (KMG) respectfully requests a variance to several requirements associated with air drilling outlined in Onshore Order 2

- Blowout Prevention Equipment (BOPE) requirements;
- Mud program requirements; and
- Special drilling operation (surface equipment placement) requirements associated with air drilling.

This Standard Operating Practices addendum provides supporting information as to why KMG current air drilling practices for constructing the surface casing hole should be granted a variance to Onshore Order 2 air drilling requirements.

The reader should note that the air rig is used only to construct a stable surface casing hole through a historically difficult lost circulation zone. A conventional rotary rig follows the air rig, and is used to drill and construct the majority of the wellbore.

More notable, KMG has used the air rig layout and procedures outlined below to drill the surface casing hole in approximately 675 wells without incident of blow out or loss of life.

Background

In a typical well, KMG utilizes an air rig for drilling the surface casing hole, an interval from the surface to surface casing depths, which varies in depth from 1,700 to 2,800 feet. The air rig drilling operation does not drill through productive or over pressured formations in KMG field, but does penetrate the Uinta and Green River Formations. The purpose of the air drilling operation is to overcome the severe loss circulation zone in the Green River known as the Bird's Nest while creating a stable hole for the surface casing. The surface casing hole is generally drilled to approximately 500 feet below the Bird's Nest.

Before the surface air rig is mobilized, a rathole rig is utilized to set and cement conductor pipe through a competent surface formation. Generally, the conductor is set at 40 feet. In some cases, conductor may be set deeper in areas that the surface formation is not found competent. This rig also drills the rat and mouse holes in preparation for the surface casing and production string drilling operations.

The air rig is then mobilized to drill the surface casing hole by drilling a 12-1/4 inch hole to just above the Bird's Nest interval with an air hammer. The hammer is then tripped and replaced with a 12-1/4 inch tri-cone bit. The tri-cone bit is used to drill to the surface casing point, approximately 500 feet below the loss circulation zone (Bird's Nest). The 9-5/8 inch surface casing is then run and cemented in place, thereby isolating the lost circulation zone.

KMG fully appreciates Onshore Order 2 well control and safety requirements associated with a typical air drilling operations. However, the requirements of Onshore Order 2 are excessive with respect to the air rig layout and drilling operation procedures that are currently in practice to drill and control the surface casing hole in KMG Fields.

Variance for BOPE Requirements

The air rig operation utilizes a properly lubricated and maintained air bowl diverter system which diverts the drilling returns to a six-inch blooie line. The air bowl is the only piece of BOPE equipment which is installed during drilling operations and is sufficient to contain the air returns associated with this drilling operation. As was discussed earlier, the drilling of the surface hole does not encounter any over pressured or productive zones, and as a result standard BOPE equipment should not be required. In addition, standard drilling practices do not support the use of BOPE on 40 feet of conductor pipe.

Variance for Mud Material Requirements

Onshore Order 2 also states that sufficient quantities of mud materials shall be maintained or readily accessible for the purpose of assuring adequate well control. Once again, the surface hole drilling operations does not encounter over pressured or productive intervals, and as a result there is not a need to control pressure in the surface hole with a mud system. Instead of mud, the air rigs utilize water from the reserve pit for well control, if necessary. A skid pump which is located near the reserve pit (see attachment) will supply the water to the well bore.

Variance for Special Drilling Operation (surface equipment placement) Requirements Onshore Order 2 requires specific safety distances or setbacks for the placement of associated standard air drilling equipment, wellbore, and reserve pits. The air rigs used to drill the surface holes are not typical of an air rig used to drill a producing hole in other parts of the US. These are smaller in nature and designed to fit a KMG location. The typical air rig layout for drilling surface hole in the field is attached.

Typically the blooie line discharge point is required to be 100 feet from the well bore. In the case of a KMG well, the reserve pit is only 45 feet from the rig and is used for the drill cuttings. The blooie line, which transports the drill cuttings from the well to the reserve pit, subsequently discharges only 45 feet from the well bore.

Typically the air rig compressors are required to be located in the opposite direction from the blooie line and a minimum of 100 feet from the well bore. At the KMG locations, the air rig compressors are approximately 40 feet from the well bore and approximately 60 feet from the blooie line discharge due to the unique air rig design. The air compressors (see attachment) are located on the rig (1250 cfm) and on a standby trailer (1170 cfm). A booster sits between the two compressors and boosts the output from 350 psi to 2000 psi. The design does put the booster and standby compressor opposite from the blooie line.

Lastly, Onshore Order 2 addresses the need for an automatic igniter or continuous pilot light on the blooie line. The air rig does not utilize an igniter as the surface hole drilling operation does not encounter productive formations.

Variance for FIT Requirements

KMG also respectfully requests a variance to Onshore Order 2, Section III, Part Bi, for the pressure integrity test (PIT, also known as a formation integrity test (FIT)). The air rig operation utilizes a 5M BOPE when drilling. This well is not an exploratory well and is being drilled in an area where the formation integrity is well known. Additionally, when an FIT is run with the mud weight as required, the casing shoe frequently breaks down and causes subsequent lost circulation when drilling the entire depth of the well.

Conclusion

The air rig operating procedures and the attached air rig layout have effectively maintained well control while drilling the surface holes in KMG Fields. KMG respectfully requests a variance from Onshore Order 2 with respect to air drilling well control requirements as discussed above.


10. Other Information:

Please refer to the attached Drilling Program.



KERR-McGEE OIL & GAS ONSHORE LP DRILLING PROGRAM







KERR-McGEE OIL & GAS ONSHORE LP

DRILLING PROGRAM

CASING PROGRAM

								DESIGN FACTORS			
	SIZE	INT	ERVA	L	WT.	GR.	CPLG.	BURST	COLLAPSE	TENSION	
CONDUCTOR	14"	(0-40'								
								3,520	2,020	453,000	
SURFACE	9-5/8"	0	to	2615	36.00	J-55	LTC	0.81*	1.65	4.81	
								7,780	6,350	201,000	
PRODUCTION	4-1/2"	0	to	9600	11.60	I-80	LTC	1.79	1.04	2.03	
								10,690	8,650	279,000	
		9600	to	10483	11.60	HCP-110	LTC	2.46	1.30	33.48	

*Burst on suface casing is controlled by fracture gradient as shoe with gas gradient above.

D.F. = 2.14

- 1) Max Anticipated Surf. Press.(MASP) (Surf Csg) = (Pore Pressure at next csg point-(0.22 psi/ft-partial evac grad x TVD of next csg point))
- 2) MASP (Prod Casing) = Pore Pressure at TD (0.22 psi/ft-partial evac gradient x TD)

(Burst Assumptions: TD = 12.2 ppg) 0.22 psi/ft = gradient for partially evac wellbore

(Collapse Assumption: Fully Evacuated Casing, Max MW) (Tension Assumptions: Air Weight of Casing*Buoy.Fact. of water)

MASP 4,225 psi

3) Maximum Anticipated Bottom Hole Pressure (MABHP) = Pore Pressure at TD

(Burst Assumptions: TD = 12.2 ppg) 0.62 psi/ft = bottomhole gradient

(Collapse Assumption: Fully Evacuated Casing, Max MW) (Tension Assumptions: Air Weight of Casing*Buoy.Fact. of water)

MABHP 6,531 psi

CEMENT PROGRAM

	FT. OF FILL	DESCRIPTION	SACKS	EXCESS	WEIGHT	YIELD
SURFACE LEAD	500'	Premium cmt + 2% CaCl	215	60%	15.60	1.18
Option 1		+ 0.25 pps flocele				
TOP OUT CMT (6 jobs)	1,200'	20 gals sodium silicate + Premium cmt	380	0%	15.60	1.18
		+ 2% CaCl + 0.25 pps flocele				
		Premium cmt + 2% CaCl				
SURFACE		NOTE: If well will circulate water to sur	face, optic	n 2 will be	utilized	
Option 2 LEAD	2,115'	Prem cmt + 16% Gel + 10 pps gilsonite	240	35%	11.00	3.82
		+ 0.25 pps Flocele + 3% salt BWOC				
TAIL	500	Premium cmt + 2% CaCl	180	35%	15.60	1.18
		+ 0.25 pps flocele				
TOP OUT CMT	as required	Premium cmt + 2% CaCl	as req.		15.60	1.18
PRODUCTION LEAD	4,593'	Premium Lite II + 0.25 pps celloflake +	440	40%	11.00	3.38
		5 pps gilsonite + 10% gel '+ 1% Retarder				
TAIL	5,890'	50/50 Poz/G + 10% salt + 2% gel	1440	40%	14.30	1.31
		+ 0.1% R-3				

^{*}Substitute caliper hole volume plus 0% excess for LEAD if accurate caliper is obtained

FLOAT EQUIPMENT & CENTRALIZERS

SURFACE

Guide shoe, 1 jt, insert float. Centralize first 3 joints with bow spring centralizers. Thread lock guide shoe.

PRODUCTION

Float shoe, 1 jt, float collar. Centralize first 3 joints & every third joint for a total of 15 bow spring centralizers.

ADDITIONAL INFORMATION

Test casing head to 750 psi after installing. Test surface casing to 1,500 psi prior to drilling out.

BOPE: 11" 5M with one annular and 2 rams. The BOPE will be installed before the production hole is drilled and tested to 5,000 psi (annular to 2,500 psi) prior to drilling out the surface casing shoe. Record on chart recorder and tour sheet. Function test rams on each trip. Maintain safety valve and inside BOP on rig floor at all times. Most rigs have top drives; however, if used, the Kelly is to be equipped with upper and lower kelly valves.


Drop Totco surveys every 2000'. Maximum allowable hole angle is 5 degrees.

Most rigs have PVT Systems for mud monitoring. If no PVT is available, visual monitoring will be utililzed.


DRILLING ENGINEER:		DATE:	
	John Huycke / Emile Goodwin	•	
DRILLING SUPERINTENDENT:		DATE:	
	John Merkel / Lovel Young	-	

^{*}Substitute caliper hole volume plus 10% excess for TAIL if accurate caliper is obtained

EXHIBIT A NBU 920-21P



SCHEMATIC DIAGRAM OF 5,000 PSI BOP STACK



ONSHORE L.P.


1099 18th Street - Denver, Colorado 80202

NBU 920-21P **WELL PAD - LOCATION LAYOUT** 281' FSL, 524' FEL SE1/4 SE1/4, OF SECTION 21, T9S, R20E, S.L.B.&M., UINTAH COUNTY, UTAH



CONSULTING, LLC 371 Coffeen Avenue Sheridan WY 82801 Phone 307-674-0609 Fax 307-674-0182

]	Scale:	1"=100'	Date:	2/17/09	SHEET NO:		
	REVISED:			BY DATE	2	2 OF 9	





Timberline

38 WEST 100 NORTH

(435) 789-1365 Engineering & Land Surveying, Inc. VERNAL, UTAH 84078

APIWeIINo:43047506270000' k:NANADARKOY2008,31_NBU_TRIBAL_2YDWGSNBU_SEC-15 TH





CROSS SECTION B-B'

NOTE: CROSS SECTION B-B' DEPICTS MAXIMUM RESERVE PIT DEPTH.

KERR-MCGEE OIL & GAS ONSHORE L.P.


1099 18th Street - Denver, Colorado 80202

NBU 920-21P
WELL PAD - CROSS SECTIONS
281' FSL, 524' FEL
SE1/4 SE1/4, OF SECTION 21, T9S, R20E,
S.L.B.&M., UINTAH COUNTY, UTAH





CONSULTING, LLC 371 Coffeen Avenue Sheridan WY 82801 Phone 307-674-0609 Fax 307-674-0182


Scale:	1"=100'	Date:	2/17/09	SHEET NO:	
REVISED):		BY DATE	3	3 OF 9




Timberline (435) 789-1365
Engineering & Land Surveying, Inc.
38 WEST 100 NORTH VERNAL, UTAH 84078












PHOTO VIEW: FROM PIT CORNER D TO LOCATION STAKE

CAMERA ANGLE: SOUTHERLY



PHOTO VIEW: FROM BEGINNING OF PROPOSED ROAD

CAMERA ANGLE: NORTHEASTERLY

Kerr-McGee Oil & Gas Onshore, LP

1099 18th Street - Denver, Colorado 80202

NBU 920-21P 281' FSL, 524' FEL $SE_{4}^{1}SE_{4}^{1}$ OF SECTION 21, T9S, R20E, S.L.B.&M. UINTAH COUNTY, UTAH.



CONSULTING, LLC 371 Coffeen Avenue Sheridan WY 82801 Phone 307-674-0609 Fax 307-674-0182

DRAWN BY: K.K.O.

DATE TAKEN: 01-07-09 DATE DRAWN: 01-15-09 REVISED:

Timberline

209 NORTH 300 WEST

TAKEN BY: D.J.S.

(435) 789-1365 Engineering & Land Surveying, Inc. VERNAL, UTAH 84078

SHEET OF 9

Kerr-McGee Oil & Gas Onshore, LP NBU 920-21P Section 21, T9S, R20E, S.L.B.&M.

PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 13.9 MILES TO THE JUNCTION OF STATE HIGHWAY 88. EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION ALONG STATE HIGHWAY 88 APPROXIMATELY 16.8 MILES TO OURAY, UTAH. FROM OURAY, PROCEED IN A SOUTHERLY DIRECTION ALONG THE SEEP RIDGE ROAD (COUNTY B ROAD 2810) APPROXIMATELY 5.9 MILES TO THE PROPOSED ACCESS ROAD. FOLLOW ROAD FLAGS IN A NORTHEASTERLY DIRECTION APPROXIMATELY 640 FEET TO THE PROPOSED LOCATION.

TOTAL DISTANCE FROM VERNAL, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 36.7 MILES IN A SOUTHERLY DIRECTION.

NBU 920-21P

Surface: 281' FSL 524' FEL (SE/4SE/4) Sec. 21 T9S R20E

> Uintah, Utah Mineral Lease: UTU 0144869

Surface Owner: Ute Indian Tribe

ONSHORE ORDER NO. 1

MULTI-POINT SURFACE USE & OPERATIONS PLAN SUBMITTED WITH SITE-SPECIFIC INFORMATION

This Application for Permit to Drill (APD) is filed under the Notice of Staking (NOS) process as stated in Onshore Order No. 1 (OSO #1) and supporting Bureau of Land Management (BLM) and Bureau of Indian Affairs (BIA) documents. An NOS was submitted showing the surface location in SE/4 SE/4 of Section 21 T9S R20E.

This Surface Use Plan of Operations (SUPO) or 13-point plan provides the site-specific information for the above-referenced wells. This information is to be incorporated by reference into the Master Development Plan (MDP) for Kerr-McGee Oil & Gas Onshore LP (Kerr-McGee). The MDP is available upon request from the BIA-Ft Duchesne Office.

An on-site meeting is scheduled for September 1-3, 2009. Please contact Raleen White at 720-929-6666 for any questions.

1. <u>Existing Roads</u>:

- A) Refer to Topo Map A for directions to the location.
- B) Refer to Topo Maps A and B for location of access roads within a 2-mile radius.

2. Planned Access Roads:

See MDP for additional details on road construction.

Approximately ± 640 ' (± 0.12 miles) of new access road is proposed. Please refer to the attached Topo Map B. No pipelines will be crossed with the new construction.

Existence of pipelines; maximum grade; turnouts; major cut and fills, culverts, or bridges; gates, cattle guards, fence cuts, or modifications to existing facilities were determined at the on-site and are typically shown on the attached Exhibits and Topo maps.

3. Location of Existing Wells Within a 1-Mile Radius:

Please refer to Topo Map C.

4. Location of Existing and Proposed Facilities:

See MDP for additional details on Existing and Proposed Facilities.

The following guidelines will apply if the well is productive.

Approximately $\pm 3,235$ ' (± 0.61 miles) of pipeline is proposed. Refer to Topo D for the existing pipeline. Appropriate surface use agreements have been or will be obtained from the Ute Indian Tribe. Pipeline segments will be welded or zaplocked together on disturbed areas in or near the location, whenever possible, and dragged into place

5. <u>Location and Type of Water Supply:</u>

See MDP for additional details on Location and Type of Water Supply.

Water for drilling purposes will be obtained from one of the following sources:

- Dalbo Inc.'s underground well located in Ouray, Utah, Sec. 32 T4S R3E, Water User Claim number 43-8496, application number 53617.
- Price Water Pumping Inc. Green River and White River, various sources, Water Right Number 49-1659, application number: a35745.

No water well is to be drilled on this lease.

6. Source of Construction Materials:

See MDP for additional details on Source of Construction Materials.

7. Methods of Handling Waste Materials:

See MDP for additional details on Methods of Handling Waste Materials.

Any produced water from the proposed well will be contained in a water tank and will then be hauled by truck to one of the pre-approved disposal sites:

RNI in Sec. 5 T9S R22E

NBU #159 in Sec. 35 T9S R21E Ace Oilfield in Sec. 2 T6S R20E MC&MC in Sec. 12 T6S R19E

Pipeline Facility in Sec. 36 T9S R20E

Goat Pasture Evaporation Pond in SW/4 Sec. 16 T10S R22E

Bonanza Evaporation Pond in Sec. 2 T10S R23E

8. Ancillary Facilities:

See MDP for additional details on Ancillary Facilities.

None are anticipated.

9. Well Site Layout: (See Location Layout Diagram)

See MDP for additional details on Well Site Layout.

All pits will be fenced according to the following minimum standards:

NBU 920-21P

- Net wire (39-inch) will be used with at least one strand of barbed wire on top of the net wire. Barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence.
- The net wire shall be no more than two inches above the ground. The barbed wire shall be three inches over the net wire. Total height of the fence shall be at least 42 inches.
- Corner posts shall be cemented and/or braced in such a manner to keep the fence tight at all times.
- Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distance between any 2 fence posts shall be no greater than 16 feet.
- All wire shall be stretched, by using a stretching device, before it is attached to corner posts.

10. Plans for Reclamation of the Surface:

See MDP for additional details on Plans for Reclamation of the Surface.

Kerr-McGee shall call the BIA for the seed mixture prior to starting interim and/or final reclamation actions.

11. <u>Surface/Mineral Ownership:</u>

The well pad and access road are located on lands owned by:

Ute Indian Tribe PO Box 70 Fort Duchesne, Utah 84026 435-722-5141

The mineral ownership is listed below:

United States of America Bureau of Land Management 170 South 500 East Vernal, UT 84078 435-781-4400

12. Other Information:

See MDP for additional details on Other Information.

'APIWeIINo:43047506270000'

13. Lessee's or Operators' Representative & Certification:

Kathy Schneebeck Dulnoan Regulatory Analyst Kerr-McGee Oil & Gas Onshore LP PO Box 173779 Denver, CO 80217-3779 (720) 929-6007 Tommy Thompson General Manager, Drilling Kerr-McGee Oil & Gas Onshore LP PO Box 173779 Denver, CO 80217-3779 (720-929-6724

Certification: All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved Plan of Operations, and any applicable Notice to Lessees.

The Operator will be fully responsible for the actions of its subcontractors. A complete copy of the approved "Application for Permit to Drill" will be furnished to the field representative(s) to ensure compliance and shall be on location during all construction and drilling operations.

Kerr-McGee Oil & Gas Onshore LP is considered to be the operator of the subject well. Kerr-McGee Oil & Gas Onshore LP agrees to be responsible under terms and conditions of the lease for the operations conducted upon leased lands.

Bond coverage pursuant to 43 CFR 3104 for lease activities is being provided by Bureau of Land Management Nationwide Bond WYB000291.

I hereby certify that I, or persons under my supervision, have inspected the proposed drill site and access route, that I am familiar with the conditions that currently exist; that I have full knowledge of the State and Federal laws applicable to this operation; that the statements made in this plan are, to the best of my knowledge, true and correct; and the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

Tarty Schil Duch	August 6, 2009
Kathy Schneebeck Dulnoan	Date

CLASS I REVIEW OF KERR-MCGEE OIL AND GAS ONSHORE LP'S 88 PROPOSED WELL LOCATIONS (T9S, R20E, SECS. 1, 14, 15, 20, 21, 22, 23, 27, 29, 32, 33, 34) UINTAH COUNTY, UTAH

By:

Jacki A. Montgomery

Prepared For:

Ute Indian Tribe
Uintah and Ouray Agency

Prepared Under Contract With:

Kerr-McGee Oil and Gas Onshore LP 1368 South 1200 East Vernal, Utah 84078

Prepared By:

Montgomery Archaeological Consultants, Inc. P.O. Box 219 Moab, Utah 84532

MOAC Report No. 08-318

March 4, 2009

United States Department of Interior (FLPMA)
Permit No. 08-UT-60122

Paleontological Assessment for Anadarko Petroleum Corp.

NBU 920-21P Ouray Quadrangle Uintah County, Utah

Prepared for

Anadarko Petroleum Corp.
and
Ute Tribe
Uintah and Ouray Reservation

Prepared by

SWCA Environmental Consultants

SWCA #UT09-14314-51



Grasslands Consulting, Inc.

4800 Happy Canyon Road, Suite 110, Denver, CO 80237 (303) 759-5377 Office (303) 759-5324 Fax

SPECIAL STATUS PLANT AND WILDLIFE SPECIES REPORT

Operator: Kerr-McGee Oil & Gas Onshore LP

Wells: NBU 920-21G, NBU 920-21I, NBU 920-21J, NBU 920-21KT, NBU 920-21L, NBU

920-21M, NBU 920-21N, NBU 920-21O, and NBU 920-21P.

Pipelines: Associated pipelines to proposed well pads

Access Roads: Associated access roads to proposed well pads

Location: Section 21, Township 9 South, Range 20 East; Uintah County, Utah


Survey-Species: Uinta Basin Hookless Cactus (*Sclerocactus wetlandicus*)

Date: July 8-9, 2009

Observer(s): Grasslands Consulting, Inc. Biologists: Dan Hamilton, Matt Kelahan, and

Jonathan Sexauer. Technicians: Chad Johnson and Daniel Ortiz.

Weather: Partly cloudy, 75-85°F, 0-5 mph winds with no precipitation.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office
P.O. Box 45155
Salt Lake City, Utah 84145-0155

IN REPLY REFER TO: 3160 (UT-922)

August 7, 2009

Memorandum

To: Assistant District Manager Minerals, Vernal District

From: Michael Coulthard, Petroleum Engineer

Subject: 2009 Plan of Development Natural Buttes Unit

Uintah County, Utah.

Pursuant to email between Diana Whitney, Division of Oil, Gas and Mining, and Mickey Coulthard, Utah State Office, Bureau of Land Management, the following wells are planned for calendar year 2009 within the Natural Buttes Unit, Uintah County, Utah.

API # WELL NAME LOCATION

(Proposed PZ WASATCH-MESA VERDE)

43-047-50613 NBU 921-23E1CS Sec 23 T09S R21E 2192 FNL 0495 FWL BHL Sec 23 T09S R21E 1767 FNL 0665 FWL

43-047-50619 NBU 921-23E4BS Sec 23 T09S R21E 2172 FNL 0530 FWL BHL Sec 23 T09S R21E 2080 FNL 0665 FWL

43-047-50620 NBU 921-23F4CS Sec 23 T09S R21E 2182 FNL 0512 FWL BHL Sec 23 T09S R21E 2425 FNL 1985 FWL

43-047-50621 NBU 921-23L1BS Sec 23 T09S R21E 2201 FNL 0477 FWL BHL Sec 23 T09S R21E 2520 FSL 0665 FWL

43-047-50623 NBU 921-28C1CS Sec 28 T09S R21E 0642 FNL 0844 FWL

BHL Sec 28 T09S R21E 0471 FNL 1985 FWL

43-047-50624 NBU 921-28C4BS Sec 28 T09S R21E 0682 FNL 0844 FWL BHL Sec 28 T09S R21E 0845 FNL 1985 FWL

43-047-50625 NBU 921-28C4CS Sec 28 T09S R21E 0702 FNL 0844 FWL BHL Sec 28 T09S R21E 1219 FNL 1985 FWL

43-047-50626 NBU 921-28D1BS Sec 28 T09S R21E 0622 FNL 0844 FWL

BHL Sec 28 T09S R21E 0622 FNL 0844 FWL

BHL Sec 28 T09S R21E 0241 FNL 0665 FWL

Page 2

 43-047-50627 NBU 920-21P
 Sec 21 T09S R20E 0281 FSL 0524 FEL

 43-047-50628 NBU 920-21N
 Sec 21 T09S R20E 0460 FSL 1527 FWL

 43-047-50629 NBU 920-21L
 Sec 21 T09S R20E 2139 FSL 0979 FWL

 43-047-50630 NBU 920-21M
 Sec 21 T09S R20E 0734 FSL 0635 FWL

This office has no objection to permitting the wells at this time.

/s/ Michael L. Coulthard

bcc: File - Natural Buttes Unit
 Division of Oil Gas and Mining
 Central Files
 Agr. Sec. Chron
 Fluid Chron


MCoulthard:mc:8-7-09

WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED:	8/6/2009	API NO.	ASSIGNED: 4	3047506270000
WELL NAME:	NBU 920-21P			
OPERATOR:	KERR-MCGEE OIL & G	SAS ONSHORE, L.P. (N2995) PHON	E NUMBER: 7	20 929-6156
CONTACT:	Danielle Piernot			
PROPOSED LOCATION:	SESE 21 090S 200E	Permit Te	ch Review:	
SURFACE:	0281 FSL 0524 FEL	Engineeri	ng Review:	<u>r</u>
воттом:	0281 FSL 0524 FEL	Geolo	gy Review:	
COUNTY:	UINTAH			
LATITUDE:	40.01413	LC	ONGITUDE: -	109.66322
UTM SURF EASTINGS:	614088.00	NO	ORTHINGS: 4	429971.00
FIELD NAME:	NATURAL BUTTES			
LEASE TYPE:				
LEASE NUMBER:	UTU 0144869	PROPOSED PRODUCING FORMATION(S):		
SURFACE OWNER:	2 - Indian	COALBED	METHANE: N	10
RECEIVED AND/OR REVIE	WED:	LOCATION AND SITING:		
 ✓ PLAT		R649-2-3.		
Bond: FEDERAL - WYB	000291	Unit: NATURAL BUTTES		
Potash		R649-3-2. General		
☑️ Oil Shale 190-5				
Oil Shale 190-3		R649-3-3. Exception		
Oil Shale 190-13		Drilling Unit		
✓ Water Permit: Permit	#43-8496	Board Cause No: Cause 173-	14	
RDCC Review:		Effective Date: 12/2/1999		
Fee Surface Agreeme	ent	Siting: 460' fr u bdry & uncom	ım. tract	
✓ Intent to Commingle		R649-3-11. Directional Drill		
Commingling Approved	i			
Comments: Presite Co	ompleted			

Stipulations:

3 - Commingling - ddoucet 4 - Federal Approval - dmason 17 - Oil Shale 190-5(b) - dmason



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

Permit To Drill

Well Name: NBU 920-21P
API Well Number: 43047506270000
Lease Number: UTU 0144869
Surface Owner: INDIAN

Approval Date: 8/20/2009

Issued to:

KERR-MCGEE OIL & GAS ONSHORE, L.P., P.O. Box 173779, Denver, CO 80217

Authority:

Pursuant to Utah Code Ann. §40-6-1 et seq., and Utah Administrative Code R649-3-1 et seq., the Utah Division of Oil, Gas and Mining issues conditions of approval, and permit to drill the listed well. This permit is issued in accordance with the requirements of Cause 173-14. The expected producing formation or pool is the WASATCH-MESA VERDE Formation(s), completion into any other zones will require filing a Sundry Notice (Form 9). Completion and commingling of more than one pool will require approval in accordance with R649-3-22.

Duration:

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date

Commingle:

In accordance with Board Cause No. 173-14, commingling of the production from the Wasatch formation and the Mesaverde formation in this well is allowed.

General:

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

Conditions of Approval:

State approval of this well does not supercede the required federal approval, which must be obtained prior to drilling.

In accordance with the Order in Cause No. 190-5(b) dated October 28, 1982, the operator shall comply with the requirements of Rules R649-3-31 and R649-3-27 pertaining to Designated Oil Shale Areas. Additionally, the operators shall ensure that the surface and or production casing is properly cemented over the entire oil shale section as defined by Rule R649-3-31. The Operator shall report the actual depth the oil shale is encountered to the division.

Notification Requirements:

The operator is required to notify the Division of Oil, Gas and Mining of the following actions during drilling of this well:

• Within 24 hours following the spudding of the well – contact Carol Daniels at 801-538-5284

API Well No: 43047506270000

(please leave a voicemail message if not available)

submit an electronic sundry notice (pre-registration required) via the Utah Oil & Gas website at https://oilgas.ogm.utah.gov

Reporting Requirements:

All reports, forms and submittals as required by the Utah Oil and Gas Conservation General Rules will be promptly filed with the Division of Oil, Gas and Mining, including but not limited to:


- Entity Action Form (Form 6) due within 5 days of spudding the well
- Monthly Status Report (Form 9) due by 5th day of the following calendar month
- Requests to Change Plans (Form 9) due prior to implementation
- Written Notice of Emergency Changes (Form 9) due within 5 days
- Notice of Operations Suspension or Resumption (Form 9) due prior to implementation
- Report of Water Encountered (Form 7) due within 30 days after completion
- Well Completion Report (Form 8) due within 30 days after completion or plugging

Approved By:

For Gil Hunt

Associate Director, Oil & Gas

	STATE OF UTAH		FORM 9	
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU 0144869			
	RY NOTICES AND REPORTS O		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: Ute Tr	
	sals to drill new wells, significantly deepen e gged wells, or to drill horizontal laterals. Use		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 920-21P	
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047506270000	
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	treet, Suite 600, Denver, CO, 80217 3779	PHONE NUMBER: 720 929-6007 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0281 FSL 0524 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: SESE Section: 21	P, RANGE, MERIDIAN: Township: 09.0S Range: 20.0E Meridian: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	☐ ACIDIZE	ALTER CASING	CASING REPAIR	
Approximate date work will start:	✓ CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
3/25/2010	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE	
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON	
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT	☐ WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION	
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR CO	MPLETED OPERATIONS. Clearly show all pertin	nent details including dates, depths, vo	olumes, etc.	
Kerr-McGee Oil & Gas Onshore LP (Kerr-McGee) respectfully requests to re-locate the spoils pile along the proposed pad location. There will be no Accepted by the additional surface disturbance due to this change. Please see the attached Utah Division of revised pad design pages for additional details. All other information remaid, Gas and Mining the same. Please contact the undersigned with any questions and FOR RECORD ONLY comments. Thank you.				
Danielle Piernot	720 929-6156	Regulatory Analyst		
SIGNATURE N/A		DATE 3/16/2010		




209 NORTH 300 WEST - VERNAL, UTAH 84078


REVISED:

3/5/10

2 OF 9

Fax 307-674-0182





CROSS SECTION B-B'

NOTE: CROSS SECTION B-B' DEPICTS MAXIMUM RESERVE PIT DEPTH.

KERR-MCGEE OIL & GAS ONSHORE L.P.

1099 18th Street - Denver, Colorado 80202

NBU 920-21P WELL PAD - CROSS SECTIONS 281' FSL, 524' FEL SE1/4 SE1/4, SECTION 21, T9S, R20E, S.L.B.&M., UINTAH COUNTY, UTAH




CONSULTING, LLC 371 Coffeen Avenue Sheridan, WY 82801 Phone 307-674-0609 Fax 307-674-0182

HORIZONTAL 0	50	100
VERTICAL 0	10	20 1" = 20'

TIMBERLINE (435) 789-1365 ENGINEERING & LAND SURVEYING, INC. 209 NORTH 300 WEST - VERNAL, UTAH 84078

65	Scale:	1"=100'	Date:	2/17/09	SHEET NO:	
	REVISED	:		RAW 3/5/10	3	3 OF 9

	STATE OF UTAH		FORM 9	
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU 0144869			
	RY NOTICES AND REPORTS O		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: Ute Tr	
	sals to drill new wells, significantly deepen e gged wells, or to drill horizontal laterals. Use		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 920-21P	
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047506270000	
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	treet, Suite 600, Denver, CO, 80217 3779	PHONE NUMBER: 720 929-6007 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0281 FSL 0524 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: SESE Section: 21	P, RANGE, MERIDIAN: Township: 09.0S Range: 20.0E Meridian: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
	☐ ACIDIZE	ALTER CASING	CASING REPAIR	
Approximate date work will start:	✓ CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME	
3/25/2010	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE	
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK	
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON	
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT	☐ WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION	
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR CO	MPLETED OPERATIONS. Clearly show all pertin	nent details including dates, depths, vo	olumes, etc.	
Kerr-McGee Oil & Gas Onshore LP (Kerr-McGee) respectfully requests to re-locate the spoils pile along the proposed pad location. There will be no Accepted by the additional surface disturbance due to this change. Please see the attached Utah Division of revised pad design pages for additional details. All other information remaid, Gas and Mining the same. Please contact the undersigned with any questions and FOR RECORD ONLY comments. Thank you.				
Danielle Piernot	720 929-6156	Regulatory Analyst		
SIGNATURE N/A		DATE 3/16/2010		




209 NORTH 300 WEST - VERNAL, UTAH 84078


REVISED:

3/5/10

2 OF 9

Fax 307-674-0182





CROSS SECTION B-B'

NOTE: CROSS SECTION B-B' DEPICTS MAXIMUM RESERVE PIT DEPTH.

KERR-MCGEE OIL & GAS ONSHORE L.P.

1099 18th Street - Denver, Colorado 80202

NBU 920-21P WELL PAD - CROSS SECTIONS 281' FSL, 524' FEL SE1/4 SE1/4, SECTION 21, T9S, R20E, S.L.B.&M., UINTAH COUNTY, UTAH



CONSULTING, LLC 371 Coffeen Avenue Sheridan, WY 82801 Phone 307-674-0609 Fax 307-674-0182

HORIZONTAL 0	50	100
VERTICAL 0	10	20 1" = 20'

TIMBERLINE (435) 789-1365 ENGINEERING & LAND SURVEYING, INC. 209 NORTH 300 WEST - VERNAL, UTAH 84078

65	Scale:	1"=100'	Date:	2/17/09	SHEET NO:	
	REVISED	:		RAW 3/5/10	3	3 OF 9

STATE OF UTAH				FORM 9	
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING					E DESIGNATION AND SERIAL NUMBER: 144869
SUNDF	RY NOTICES AND REPORT	S ON	I WELLS	6. IF IN	IDIAN, ALLOTTEE OR TRIBE NAME:
	sals to drill new wells, significantly deepe ugged wells, or to drill horizontal laterals.				or CA AGREEMENT NAME: RAL BUTTES
1. TYPE OF WELL Gas Well					L NAME and NUMBER: 20-21P
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.				NUMBER: 506270000
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	PH treet, Suite 600, Denver, CO, 80217 377		UMBER: 720 929-6007 Ext		D and POOL or WILDCAT: RAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0281 FSL 0524 FEL QTR/QTR, SECTION, TOWNSHI	IP, RANGE, MERIDIAN:			COUNT	H
	Township: 09.0S Range: 20.0E Meridian	: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICA	ATE N.	ATURE OF NOTICE, REPORT,	OR OTI	HER DATA
TYPE OF SUBMISSION			TYPE OF ACTION		
	☐ ACIDIZE		ALTER CASING		CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS		CHANGE TUBING		CHANGE WELL NAME
8/20/2010	☐ CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS		CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN		FRACTURE TREAT		NEW CONSTRUCTION
Date of work completion.	OPERATOR CHANGE		PLUG AND ABANDON		PLUG BACK
☐ SPUD REPORT	☐ PRODUCTION START OR RESUME		RECLAMATION OF WELL SITE		RECOMPLETE DIFFERENT FORMATION
Date of Spud:	REPERFORATE CURRENT FORMATION		SIDETRACK TO REPAIR WELL		TEMPORARY ABANDON
	☐ TUBING REPAIR		VENT OR FLARE		WATER DISPOSAL
DRILLING REPORT Report Date:	☐ WATER SHUTOFF		SI TA STATUS EXTENSION	1	APD EXTENSION
	☐ WILDCAT WELL DETERMINATION		OTHER	отн	ER:
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. Kerr-McGee Oil & Gas Onshore, L.P. (Kerr-McGee) respectfully requests an extension to this APD for the maximum time allowed. Please contact the undersigned with any questions and/or comments. Thank you. Approved by the Utah Division of Oil, Gas and Mining Date: August 23, 2010 By:					
NAME (PLEASE PRINT) Danielle Piernot	PHONE NUMBE 720 929-6156	R	TITLE Regulatory Analyst		
SIGNATURE N/A			DATE 8/18/2010		



Sig

The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047506270000

API: 43047506270000 **Well Name:** NBU 920-21P

Location: 0281 FSL 0524 FEL QTR SESE SEC 21 TWNP 090S RNG 200E MER S

Company Permit Issued to: KERR-MCGEE OIL & GAS ONSHORE, L.P.

Date Original Permit Issued: 8/20/2009

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

ire revi	sion. Following is a checklis	t of some items related to the	application, which should be verified.
	ated on private land, has the ed? Yes No	e ownership changed, if so, has	s the surface agreement been
	any wells been drilled in the requirements for this locat		which would affect the spacing or
	nere been any unit or other s proposed well? 🔵 Yes (could affect the permitting or operation
	there been any changes to the the proposed location?		ership, or rightof- way, which could
• Has th	ne approved source of wate	r for drilling changed? 🔘 Yes	s 📵 No
		anges to the surface location or iscussed at the onsite evaluation	r access route which will require a on? 🔲 Yes 📵 No
• Is bor	nding still in place, which co	overs this proposed well?	Approved by the Yes No Utah Division of Oil, Gas and Mining
		Date: 8/18/2010	
Title:	Regulatory Analyst Represer	iting: KERR-MCGEE OIL & GAS O	NSHOR Pate: August 23, 2010
			M 160 00 I

By: Dod

Sundry Number: 16641 API Well Number: 43047506270000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOURC	FS	FORM 9
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU 0144869		
SUNDI	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: Ute Tr
	sals to drill new wells, significantly deepen ugged wells, or to drill horizontal laterals. I		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 920-21P
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047506270000
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	PHO Street, Suite 600, Denver, CO, 80217 3779	NE NUMBER: 720 929-6515 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0281 FSL 0524 FEL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSH	IP, RANGE, MERIDIAN: Township: 09.0S Range: 20.0E Meridian: S	S	STATE: UTAH
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPORT,	OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	☐ ACIDIZE	☐ ALTER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS	☐ CHANGE TUBING	CHANGE WELL NAME
7/12/2011	☐ CHANGE WELL STATUS	☐ COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	D DEEPEN	☐ FRACTURE TREAT	☐ NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE	☐ PLUG AND ABANDON	☐ PLUG BACK
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	☐ TUBING REPAIR	☐ VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT	☐ WATER SHUTOFF	☐ SI TA STATUS EXTENSION	✓ APD EXTENSION
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:
12 DESCRIBE DROBOSED OF CO	MPLETED OPERATIONS. Clearly show all per	rtinent details including dates, denths	volumes etc
1	ias Onshore, L.P. (Kerr-McGee		volumes, etc.
extension to this A	APD for the maximum time all	owed. Please contact the	
undersigned	with any questions and/or cor	mments. Thank you.	Approved by the Utah Division of
			Oil, Gas and Mining
			07/12/2011
		D	Pate: 07/12/2011
			R.00cal VV
		•	ay: Doo Africa
NAME (PLEASE PRINT) Gina Becker	PHONE NUMBER 720 929-6086	TITLE Regulatory Analyst II	
SIGNATURE N/A		DATE 7/12/2011	

Sundry Number: 16641 API Well Number: 43047506270000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047506270000

API: 43047506270000 **Well Name:** NBU 920-21P

Location: 0281 FSL 0524 FEL QTR SESE SEC 21 TWNP 090S RNG 200E MER S

Company Permit Issued to: KERR-MCGEE OIL & GAS ONSHORE, L.P.

Date Original Permit Issued: 8/20/2009

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

	ated on private land, has the ed? 📗 Yes 📵 No	e ownership changed, if so, has the s	urface agreement been
	any wells been drilled in the requirements for this locati	e vicinity of the proposed well which on? Yes No	would affect the spacing or
	here been any unit or other as proposed well?	agreements put in place that could a No	ffect the permitting or operation
	there been any changes to t the proposed location?	the access route including ownership Yes No	, or rightof- way, which could
• Has tl	he approved source of water	r for drilling changed? 🔵 Yes 🍺	No
		nges to the surface location or accesiscussed at the onsite evaluation?	
• Is bo	nding still in place, which co	vers this proposed well? 🌘 Yes 🤇) No
Signature:	Gina Becker	Date: 7/12/2011	

Title: Regulatory Analyst II Representing: KERR-MCGEE OIL & GAS ONSHORE, L.P.



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining JOHN R. BAZA Division Director

May 9, 2012

Jenn Hawkins Anadarko Petroleum Corporation 1099 18th Street, Suite 1800 Denver, CO 80202

Re:

APDs Rescinded for Anadarko Petroleum Corporation

Uintah County

Dear Ms. Hawkins:

Enclosed find the list of APDs that you requested to be rescinded. No drilling activity at these locations has been reported to the division. Therefore, approval to drill these wells is hereby rescinded, effective May 2, 2012.

A new APD must be filed with this office for approval <u>prior</u> to the commencement of any future work on the subject location.

If any previously unreported operations have been performed on this well location, it is imperative that you notify the Division immediately.

Sincerely,

Diana Mason

Environmental Scientist

land the laser

cc:

Well File

Bureau of Land Management, Vernal

SITLA, Ed Bonner



4304750055	NBU 753-32E	4304740374	NBU 705-26E
4304750683	NBU 634-12EX	4304750123	NBU 920-12N
4304740346	NBU 921-15N1S	4304750143	NBU 920-13J
4304740347	NBU 921-14M3S	4304750751	NBU 920-21G
4304740348	NBU 921-22A1S	4304750756	NBU 1022-35I1CS
4304750089	NBU 921-1503T	4304750757	NBU 1022-35I4BS
4304740441	NBU 1022-25G2S	4304750758	NBU 1022-35J1CS
4304740442	NBU 1022-25G4S	4304750759	NBU 1022-35J4CS
4304740443	NBU 1022-25G3S	4304740380	NBU 920-13D
4304750852	FEDERAL 920-230	4304750155	FEDERAL 920-240
4304751026	NBU 921-12K	4304750769	NBU 1022-35K4CS
4304751027	NBU 921-12L	4304750770	NBU 1022-35N1CS
4304751028	NBU 921-12M	4304750771	NBU 1022-3501BS
4304751039	NBU 920-210	4304750772	NBU 1022-3501CS
4304750697	NBU 687-30E	4304750791	NBU 921-100
4304750811	NBU 699-25E	4304750792	NBU 921-10M
4304740153	NBU 1022-05JT	4304740439	NBU 1022-24P2S
4304740135	NBU 921-15MT	4304740440	NBU 1022-24P4S
4304750468	NBU 738-30E		
4304739369	NBU 922-180		
4304739372	NBU 922-20E		
4304740184	NBU 921-30FT		
4304740217	NBU 759-29E		
4304740218	NBU 737-30E		
4304750461	NBU 1022-2402S		
4304740267	NBU 704-26E		
4304740240	NBU 702-26E		
4304740241	NBU 703-26E		
4304750578	NBU 920-14B		
4304750579	NBU 920-14A		
4304740268	NBU 701-26E		
4304750627	NBU 920-21P		
4304750628	NBU 920-21N		
4304750682	NBU 921-12J		
4304750695	NBU 921-12N		
4304750111	NBU 921-11GT		
4304750112	NBU 921-11HT		
4304750118	NBU 740-30E		

United States Department of the Interior



BUREAU OF LAND MANAGEMENT

Green River District-Vernal Field Office 170 South 500 East Vernal, UT 84078 (435) 781-4400 Fax: (435) 781-4410

(435) 781-4400 Fax: (435) 781-4410 http://www.blm.gov/ut/st/en/fo/vernal.html



MAY 1 4 2012

IN REPLY REFER TO: 3160 (UTG011)

Julie Jacobson Anadarko Petroleum Corporation Kerr McGee Oil & Gas Onshore LP 1099 18th Street, Suite 600 Denver, CO 80202

43 047 50627

Re:

Request to Return APD Well No. NBU 920-21P SESE, Sec. 21, T9S, R20E Uintah County, Utah Lease No. UTU-0144869 Natural Buttes Unit

Dear Ms. Jacobson:

The Application for Permit to Drill (APD) for the above referenced well received in this office on August 11, 2009, is being returned unapproved per a request to this office in an email message from you received on April 23, 2012. If you intend to drill at this location at a future date, a new Application for Permit to Drill must be submitted.

If you have any questions regarding APD processing, please contact Cindy Severson at (435) 781-4455.

Sincerely,

Jerry Kenczka

Assistant Field Manager Lands & Mineral Resources

Enclosures

CC:

UDOGM

RECEIVED MAY 2 2 2012

DIV. OF OIL, GAS & MINING